

12NC/Fx: 859991541970

## GTIN (EAN) code: 8003437230929

DIMENSION	<b>MEAS</b>	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	452	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	545	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mm
Space in front, which is required to install bottom trim	7	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	45	mm
Minimum area for inbound ventilation cavity (tall cabinet)	252	cm <sup>2</sup>
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	45	mm
Minimum area for outbound ventilation cavity (tall cabinet)	252	cm <sup>2</sup>
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm <sup>2</sup>
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm <sup>2</sup>

Width of the front 22 mm Maximum depth all protruding elements, e.g. handles, controls 0 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 80 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle thickness 0 mm MIN Height of the product body 442 mm MAX Height of the product body 442 mm Width of the product body 450 mm Full depth of product body 450 mm	DIMENSION		EASURE	
Width of the front 22 mm Maximum depth all protruding elements, e.g. handles, controls 0 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 10 mm Projection of front in relation to housing of appliance 10 mm Aspailance, if height is adjustable 10 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 10 mm Frontal handle thickness 0 mm Frontal handle thickness 0 mm Max Height of the product body 442 mm Max Height of the product body 442 mm More the product body 450 mm Lude the product body 450 mm Appliance and be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door 10 mm Appliance Flap door 10 mm Projection of front incl. controls when door is opened totaly. At the side where the hinge is more more peth from tend of the niche to the front end of the freespace of the retrace 0 mm Appliance other 10 mm Appliance 10 mm Appl	APPLIANCE			
Depth of the front  Maximum depth all protruding elements, e.g. handles, controls  Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees  Projection of front in relation to housing of appliance  Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  O mr  Frontal handle width  O mr  MIN Height of the product body  Width of the product body  Width of the product body  Full depth of product excluding protruding interface elements  - mr  - mr  - mr  - mr  - mr  - Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of front incl. controls when door is opened totaly. At the side where the hinge is morn and post of the product of opened front at the side where the hinge is fixed  Depth from front end of the niche to the front end of the freespace of the retrace  O mr  Appliance Sides wing door  Depth from front end of the niche to the front end of the freespace of the retrace	Height of the front	455	mm	
Maximum depth all protruding elements, e.g. handles, controls  Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees  Projection of front in relation to housing of appliance  Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  Onmr  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Moth of the product body  Moth of the product body  Moth of the product body  Full depth of product excluding protruding interface elements	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm MAX Height of the product body 442 mm Width of the product body 560 mm Full depth of product excluding protruding interface elements 501 mm	Depth of the front	22	mm	
neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Frontal handle thickness O mr Frontal handle width O mr MIN Height of the product body MAX Height of the product body Width of the product body Full depth of product excluding protruding interface elements  - mr mr mm mm mm mm - manual manu	Maximum depth all protruding elements, e.g. handles, controls	0	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  O mr Frontal handle thickness  O mr Frontal handle width  NIN Height of the product body  MAX Height of the product body  Width of the product body  Full depth of product body  Full depth of product excluding protruding interface elements  O mr  - mr mm mm - mm - mm - mm -	· · · · · · · · · · · · · · · · · · ·	0	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness O mm Frontal handle width O mm MIN Height of the product body MAX Height of the product body MAX Height of the product body Depth of the product body Full depth of product excluding protruding interface elements  - mm mm - mm - mm - mm - mm - mm	Projection of front in relation to housing of appliance	10	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  O mr Frontal handle thickness  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Width of the product body  Depth of the product body  Full depth of product excluding protruding interface elements  - mr mr mr mr - Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of opened front at the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  o mr -	• • • • • • • • • • • • • • • • • • • •	2	mm	
dimension Height from bearing area of appliances and lower handle Frontal handle thickness O mm Frontal handle width O mm MIN Height of the product body MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements  O mm  mm  mm  mm  mm  mm  - Mappliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace  0 mm  Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	When product panel is missing, set to 0	80	mm	
Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm MAX Height of the product body 442 mm Width of the product body 560 mm Depth of the product body 450 mm Full depth of product excluding protruding interface elements 501 mm - Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally 85 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm  MIN Height of the product body 442 mm M422 mm M442 mm		207	mm	
Frontal handle width 0 mm  MIN Height of the product body 442 mm  MAX Height of the product body 560 mm  Depth of the product body 450 mm  Full depth of product excluding protruding interface elements 501 mm  - m	Height from bearing area of appliances and lower handle	0	mm	
MIN Height of the product body  MAX Height of the product body  Width of the product body  Depth of the product body  Full depth of product excluding protruding interface elements	Frontal handle thickness	0	mm	
MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements 501 mm	Frontal handle width	0	mm	
Width of the product body  Depth of the product body  Full depth of product excluding protruding interface elements  - mm  mm  -	MIN Height of the product body	442	mm	
Depth of the product body Full depth of product excluding protruding interface elements 501 mm - mm mm -	MAX Height of the product body	442	mm	
Full depth of product excluding protruding interface elements  - mm  - m	Width of the product body	560	mm	
- mm	Depth of the product body	450	mm	
- mm	Full depth of product excluding protruding interface elements	501	mm	
- mm	-	-	mm	
- mm	-	-	mm	
- mm	-	-	mm	
- mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  - mm -	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  - mm  No  Appliance Flap door  No  No  No  No  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  No  No  No  No  No  Appliance Flap door  90 mm  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is fixed  0 mm  Appliance other	-	-	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 3 mm Maximum angle when flap door is opened totally 90 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 85 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	-	-	mm	
Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No	" No		
Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm	Appliance Flap door			
Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  O mm	Projection of the opened flap in relation to bearing area	3	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  O mm	Maximum angle when flap door is opened totally	90	mm	
mounted  Lateral projection of opened front at the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm	Appliance Side swing door			
Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm	, ,	s 0	mm	
Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Maximum angle when door is opened totally	85	mm	
	Appliance other			
Height from niche to bottom end of freespace for the retrace 0 mm	Depth from front end of the niche to the front end of the freespace of the retrace	0	mm	
	Height from niche to bottom end of freespace for the retrace	0	mm	