

Series 2, free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, White KGN36NWEA





The NoFrost bottomfreezer with MultiBox: Has enough room for all your food

- **Perfect Fit:** place your fridge right next to walls and other appliances to save space.
- LED interior light: Illuminates the refrigerator evenly and glarefree, and lasts for its entire life.

Technical Data

Energy Efficiency Class (Regulation (EU) 2017/1369): E Average annual energy consumption in kilowatt hour per year (kWh/a) (EU) 2017/1369: 239 kWh/annum

Sum of volume of frozen compartments (EU 2017/1369): 89 I Sum of volume of chill compartments (EU 2017/1369): 216 I Airborne acoustical noise emissions (EU 2017/1369): 42 dB(A) re 1 pW

Airborne acoustical noise emission class (EU 2017/1369): D

Built-in / Free-standing: Free-standing

Number of compressors: 1

Number of independent cooling systems: 1

Width of the appliance: 600 mm Depth of the product: 660 mm

Net weight: 61.9 kg

Door panel options: Not possible Door hinge: Right reversible

Number of Adjustable Shelves in fridge compartment: 3

Shelves for Bottles: No Interior ventilator: No Reversible Door Hinge: Yes

Length electrical supply cord: 240 cm

Noise level: 42 dB(A) re 1 pW Multi-Flow Air Tower: Yes Fast cooling switch: No Fast freezing switch: Yes

Temperature Controlled Drawer: No Humidity Control Drawer: No

Number of Door Bins - Refrigerator: 4 Door bin adjustability - Refrigerator: No

Tilt-out door bins in fridge: No Gallon wide door bins: Yes Number of Gallon storage: 1 Motorized Shelf: No

Material of the shelves: Safety glass Door opened indicator freezer: No Automatic motor-driven ice-maker: No

Connection Rating: 100 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50 Hz

Storage Period in Event of Power Failure (h): 12 h

Approval certificates: CE, VDE
Main colour of product: White
Door panel options: Not possible
Noise level: 42 dB(A) re 1 pW
Energy Star Qualified: No
Approval certificates: CE, VDE
Plug type: Gardy plug w/ earthing

Required cutout/niche size for installation (in): $x \times x$ Dimensions of the packed product: $75.59 \times 26.10 \times 30.55$

Net weight: 136.000 lbs Gross weight: 149.000 lbs





Series 2, free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, White KGN36NWEA

The NoFrost bottomfreezer with MultiBox: Has enough room for all your food

General Information

- 3 freezer drawers, incl. 1 Big Box
- Vario Zone removable glass shelves for extra space
- Freezing possible in all freezer compartments
- Super Cooling: No
- Active Warning System by Temperatur increase

Performance and consumption

Design and Styling

- Doors White, side panels white
- Integrated horizontal handle
- LED with Soft Start in fridge section

Convenience & Safety

- NoFrost never again defrosting!
- LED electronic control
- Super Freezing: manual activation

Fridge Compartment

- Multi Airflow-System
- 4 safety glass shelves of which 3 are height adjustable
- 4 door bins

Freshness System

- MultiBox: transparent drawer with wave bottom, ideal for the storage of fruits and vegetables

Freezer Section

- 3 freezer drawers, incl. 1 EasyAccess Freezer Box

Dimensions

- Dimensions (H x W x D): 186.0 cm x 60.0 cm x 66.0 cm

Technical Information

- Door right hinged, reversible
- Height adjustable front feet
- Connected load: 100 W
- Nominal voltage: 220 240 V

Accessories

Country Specific Options


- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the attached distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.


Environment and Safety

Installation



Series 2, free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, White **KGN36NWEA**





Dimension A:
In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm