


Series 8, Flex induction hob, 60 cm, Black PXE675DC1E













- **DirectSelect Premium:** Direct, simple selection of the desired cooking zone, power and additional functions.
- Flexinduction Zone: Get more flexibility by combining the cooking zones into one big zone for placing small pots and large cookware.
- **PerfectFry:** For perfect browning of roasted foods thanks to sensor control with 5 power levels.
- ComfortProfil: Elegant, appealing design with bevelled front and metal strips on the side.
- **MoveMode:** the automatic setting of cooking levels allows fast boiling on the front, cooking on the middle and simmering on the rear cooking zone.

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) : 51 x 560-560 x

490-500 mm

Width of the appliance : 606 mm Dimensions : 51 x 606 x 527 mm

Dimensions of the packed product (HxWxD) : 126 x 753 x 603

mm

Net weight : 14.1 kg Gross weight : 15.3 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic

Color of surface : Black

Approval certificates : AENOR, CE Length electrical supply cord : 110 cm

Sealed Burners : No heating with booster : All

Power of 2nd heating element (kW): 3.3 kW
Power of 5th heating element (kW): 1.4 kW
Power of heating element (kW in boost): [3.7] kW

: 3.7 kW

Power of 5th heating element (kW in boost): [2.2] kW

Connection Rating: 7400 W Voltage: 220-240 V Frequency: 60; 50 Hz Main colour of product: Black

Energy input : Electric

Approval certificates: AENOR, CE

Plug type: no plug (electrical connection by electrician)

Appliance Dimensions (h x w x d) (in) : + x x

Dimensions of the packed product: 4.96 x 23.74 x 29.64

Net weight: 31.000 lbs Gross weight: 34.000 lbs

Total number of positions that can be used at the same time: 4

Length electrical supply cord: 110 cm

Required niche size for installation (HxWxD) : 51 x 560-560 x

490-500 mm

Dimensions : 51 x 606 x 527 mm

Dimensions of the packed product (HxWxD): 126 x 753 x 603

mm

Net weight : 14.1 kg Gross weight : 15.3 kg

