


Induction **ARIA+** 60

FHH 600 ID TC BK



- Multifunction Touch Control
- VCR Black finishing
- 4 Cooking zones (2 vertical bridge zones)
- 9 Power levels + Booster
- Temperature keeping function
- Chef function
- End-of-cooking timer
- Power limiter (insertable)
- Integrated suction hood
- Suction booster
- A++ Energy Class



Features

Induction hob with integrated extractor hood equipped with a patented waterproof motor: in one appliance, the performance of induction combined with the functionality of on-surface extraction. Among the various functions available, the Chef function allows you to preset cooking zones with differentiated temperatures. It also includes adjustable delayed auto-off functions, grease filter maintenance warning, ceramic activated carbon filter regeneration light warning, and automatic hood shut-off when the flap is closed. In addition to the Grease Filter Kit, it is included the scraper for surface cleaning. Available upon request: Connection Kit and Charcoal Filter Kit.



VCR BLACK
FHH 600 ID TC BK
EAN 8019801032020

INDUCTION HOB

GLASS CERAMIC INDUCTION HOB



FHH 600 ID TC BK		
Dimensions	60	
Technology	B4 Induction	
Glass finishing	VCR Black	
Controls	Touch	
Version	Suction	
Energy efficiency class	A ++	
INDUCTION HOB		
Power Absorption Limiter	•	
Power levels	9 + P	
Booster	5 minutes	
Commands	Multifunction Touch Control	
Power levels Slider Indicator	•	
Residual heat indicator for each zone	•	
FUNCTIONS		
	Pause and restart function	Pot detection
	Overheating protection	Timer
	Child lock	Automatic fast heating
	Melt function (44 °C)	Chef function
	Single zone timer	Bridge function
	Acoustic buzzer	Lock
INDUCTION ZONES		
Zone Dimension	220 X 190 mm	
Bridge Function	2 Vertical Bridge Zones	
Max Power Zone (L9)	2100W	
Booster Zone Power	3000W	
HOOD		
Adjustable delayed automatic shutdown	•	
Grease filter maintenance warning	•	
Ceramic filter regeneration LED warning	•	
Internal water drain valve	•	
Dishwasher-safe grease filter	•	
Regenerable ceramic odor filter removable from the top (optional)	•	
Automatic hood shut-off when flap is closed	•	
Motor positioned under the glass	•	
Patented waterproof motor	•	
Air exhaust plastic connection	•	
Maximum flow rate (m3 / h)	700	
Pressure (Pa)	540	
Motor power (W)	220	
Voltage (V)	220/240	
Frequency (Hz)	50/60	
Sound power max vel. dB(A)	62	
Commands	Multifunction Touch Control	
DIMENSIONS		
Width x Height x Depth (mm)	600 x 249 x 520	
Cutout Width x Depth (mm)	560 x 480	
POWER RATING		
Max absorbed electrical power (kW)	7.36	
Voltage (V)	220/240	
Frequency (Hz)	50/60	
DOCUMENTATION		
Installation & Use Manual	IT - EN - FR - DE - ES - RU	