


## Induction ARIA+ 80

FHH 800 ID TC BK



- Multifunction Touch Control
- VCR Black finishing
- 4 Cooking zones (2 vertical bridge zones)
- 9 Power levels + Booster
- Temperature keeping function
- Chef function
- End-of-cooking timer
- Power limiter (insertable)
- Integrated suction hood
- Suction booster
- A++ Energy Class



## Features

Induction hob with integrated extractor hood equipped with a patented waterproof motor: in one appliance, the performance of induction combined with the functionality of on-surface extraction. Among the various functions available, the Chef function allows you to preset cooking zones with differentiated temperatures. It also includes adjustable delayed auto-off functions, grease filter maintenance warning, ceramic activated carbon filter regeneration light warning, and automatic hood shut-off when the flap is closed. In addition to the Grease Filter Kit, it is included the scraper for surface cleaning. Available upon request: Connection Kit and Charcoal Filter Kit.



VCR BLACK  
FHH 800 ID TC BK  
EAN 8019801032013

# INDUCTION HOB

GLASS CERAMIC INDUCTION HOB



| FHH 800 ID TC BK  |                             |                        |
|---|-----------------------------|------------------------|
| Dimensions  | 80                          |                        |
| Technology  | B4 Induction                |                        |
| Glass finishing   | VCR Black                   |                        |
| Controls  | Touch                       |                        |
| Version   | Suction                     |                        |
| Energy efficiency class   | A ++                        |                        |
| INDUCTION HOB   |                             |                        |
| Power Absorption Limiter  | •                           |                        |
| Power levels  | 9 + P                       |                        |
| Booster   | 5 minutes                   |                        |
| Commands  | Multifunction Touch Control |                        |
| Power levels Slider Indicator                                     | •                           |                        |
| Residual heat indicator for each zone                             | •                           |                        |
| FUNCTIONS   |                             |                        |
|   | Pause and restart function  | Pot detection          |
|   | Overheating protection      | Timer                  |
|   | Child lock                  | Automatic fast heating |
|   | Melt function (44 °C)       | Chef function          |
|   | Single zone timer           | Bridge function        |
|   | Acoustic buzzer             | Lock                   |
| INDUCTION ZONES   |                             |                        |
| Zone DImension  | 220 X 190 mm                |                        |
| Bridge Function   | 2 Vertical Bridge Zones     |                        |
| Max Power Zone (L9)   | 2100W                       |                        |
| Booster Zone Power  | 3000W                       |                        |
| HOOD  |                             |                        |
| Adjustable delayed automatic shutdown                             | •                           |                        |
| Grease filter maintenance warning                                 | •                           |                        |
| Ceramic filter regeneration LED warning                           | •                           |                        |
| Internal water drain valve  | •                           |                        |
| Dishwasher-safe grease filter                                     | •                           |                        |
| Regenerable ceramic odor filter removable from the top (optional) | •                           |                        |
| Automatic hood shut-off when flap is closed                       | •                           |                        |
| Motor positioned under the glass                                  | •                           |                        |
| Patented waterproof motor   | •                           |                        |
| Air exhaust plastic connection                                    | •                           |                        |
| Maximum flow rate (m3 / h)  | 700                         |                        |
| Pressure (Pa)   | 540                         |                        |
| Motor power (W)   | 220                         |                        |
| Voltage (V)   | 220/240                     |                        |
| Frequency (Hz)  | 50/60                       |                        |
| Sound power max vel. dB(A)  | 62                          |                        |
| Commands  | Multifunction Touch Control |                        |
| DIMENSIONS  |                             |                        |
| Width x Height x Depth (mm)                                       | 800 x 249 x 520             |                        |
| Cutout Width x Depth (mm)   | 750 x 490                   |                        |
| POWER RATING  |                             |                        |
| Max absorbed electrical power (kW)                                | 7.36                        |                        |
| Voltage (V)   | 220/240                     |                        |
| Frequency (Hz)  | 50/60                       |                        |
| DOCUMENTATION   |                             |                        |
| Installation & Use Manual   | IT - EN - FR - DE - ES - RU |                        |