

WCW707HTSBUK

12NC/Fx: 859991680380

GTIN (EAN) code: 8003437397127

DIMENSION	MEAS	SUR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	453	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mn
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mn
Space in front, which is required to install bottom trim	8	mn
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mn
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mn
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mn
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mn
Minimum area for inbound ventilation cavity (base cabinet)	0	cm
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm

Depth of the front20mmMaximum depth all protruding elements, e.g. handles, controls0mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front in relation to bousing of appliance0mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 097mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle thickness13mmMIN Height of the product body442mmMil Height of the product body442mmWidth of the product body559mmDepth of the product body543mmMunimum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter raximum air outlet0mmAppliance Stale swing door0mmAppliance Stale subse for other appliances from the same manufacturer. Default is "No"NoProjection of the pered flap in relation to bearing area6mmMaximum height form bottom line hood totally63mmFull depth of product excluding protruding area0mmDiameter maximum air outlet0m	DIMENSION		
Width of the front595mmDepth of the front20mmMaximum depth all protruding elements, e.g. handles, controls0mmIateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees13mmProjection of front in relation to bearing area of the appliance.13mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable97mmWhen product panel is missing, set to 097mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle thickness13mmMUN Height of the product body442mmMiL Height of the product body543mmJuil depth of product body543mmJuil depth of product body543mmJuil depth of product body543mmJuil depth of product body0mmJuameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the opened flap in relation to bearing area0mmAppliance flap door111Projection of the opened flap in relation to bearing area0mmApplianc	APPLIANCE		
Depth of the front20mmMaximum depth all protruding elements, e.g. handles, controls0mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees13mmProjection of front in relation to busing of appliance13mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable97mmWhen product panel is missing, set to 097mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension344mmFrontal handle thickness13mmFrontal handle thickness13mmMIN Height of the product body442mmMX Height of the product body442mmWidth of the product body559mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter minimum air outlet0mmAppliance and be used as base for other appliances from the same manufacturer. Default is "No"ApplianceAppliance Flap doormmmmAppliance Flap doormmAppliance flap or or outlet, only area0mmAppliance flap doormmmmAppliance flap doormmmmAppliance flap doormmmmAppliance flap doormmmmAppliance flap doormmmmAppliance flap doormm<	Height of the front	455	mm
Maximum depth all protruding elements, e.g. handles, controls0mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees13mmProjection of front in relation to bearing area of the appliance.13mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable97mmWhen product panel is missing, set to97mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle thickness13mmMIN Height of the product body442mmWidth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter flap in relation to bearing area0mmProjection of the opened flap in relation to bearing area0mmAppliance are bused as base for other appliances from the same manufacturer. Default is "No"NoProjection of the opened flap in relation to bearing area0mmAppliance Side swing door10mmLateral projection of poneed front at the side where the hinge is fixed0mm </td <td>Width of the front</td> <td>595</td> <td>mm</td>	Width of the front	595	mm
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front in relation to housing of appliancenmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 097mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle thickness0mmMIN Height of the product body442mmMX Height of the product body442mmMild to fthe product body559mmDepth of the product body563mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmAppliance Flap door0mmAppliance Flap door0mmAppliance flap door0mmAppliance flap door0mmMinimum angle when flap dor is opened totally. At the side where the hinge is0Appliance flap door0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmAppliance Calle swing door0mmLateral projection of the nelation to bearing area0m	Depth of the front	20	mm
neighbour front more than 90 degrees13mmProjection of front in relation to housing of appliance13mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 097mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle width0mmMAX Height of the product body442mmWidth of the product body559mmDepth of the product body543mmWidth of the product body543mmNumm height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmNoProjection of front in relation to bearing area0mmHeight from bottom line relation to bearing area0mmProjection of the rear flap in relation to bearing area0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door10mmProjection of the opened flap in relation to bearing area0mmAppliance Carbe use as base for other appliances from the same manufacturer. Default is "No"NoAppliance Side swing door111Lateral pr	Maximum depth all protruding elements, e.g. handles, controls	0	mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable 97 mm Space in front, which is required to guarantee full operability. The most protruding part gives this 340 mm dimension 134 mm Frontal handle thickness 134 mm Frontal handle thickness 13 mm MNN Height of the product body 442 mm MAX Height of the product body 442 mm MAX Height of the product body 442 mm Min Height of the product body 559 mm Depth of the product body 559 mm Full depth of product excluding protruding interface elements 563 mm Minimum height from bottom line hood to top line air outlet 0 mm Diameter maximum air outlet 0 mm Projection of the rear flap in relation to bearing area 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door 14 metation to bearing area 6 mm Maximum angle when flap door is opened totally. At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally. At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance cather 0 mm Maximum angle when door is opened totally Appliance cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Appliance cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Appliance Cather 0 mm Maximum angle when door is opened totally Applianc		0	mm
appliance, if height is adjustable97mmWhen product panel is missing, set to 097mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle width0mmMIN Height of the product body442mmMAX Height of the product body442mmWidth of the product body543mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmDiameter mainum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Side swing door6mmAppliance Side swing door6mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when flap door is opened totally0mmmmAppliance Side swing door0mmmmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmAppliance Other0mm0mmDiameter Maximum angle when door is opened totally0mmMmAppliance Side swing door0 <td>Projection of front in relation to housing of appliance</td> <td>13</td> <td>mm</td>	Projection of front in relation to housing of appliance	13	mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension340mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle width0mmMIN Height of the product body442mmMXA Height of the product body442mmWidth of the product body559mmDepth of the product body543mmWidth of product excluding protruding interface elements563mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter minimum air outlet0mmDiameter molinum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Side swing door6mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmAppliance other0mmmmAppliance other0mmmmAppliance other0mmmmAppliance other0mmAppliance other0mmAppliance flap door is opened totally. At the side where the hinge is fixed0mmAppliance Side swing door0mmmmLateral projection of opened front at the side where the hinge is fixe		0	mm
dimension344mmHeight from bearing area of appliances and lower handle344mmFrontal handle thickness13mmFrontal handle width0mmMIN Height of the product body442mmMAX Height of the product body442mmMAX Height of the product body559mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmNoMaxinua height hop cauted to be para and the projection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoMaximum angle when flap door is opened totally. At the side where the hinge is fixed0mmAppliance Side swing doorIIIIILateral projection of opened front at the side where the hinge is fixed0mmmmAppliance other0mmMaximum angle when door is opened totally. At the side where the hinge is fixed0mmAppliance other0mmMaximum angle when door is opened totally. At the side where the hinge is fixed0mmAppliance other0mmMaximum angle when door is opened totally. At the side where the hinge is fixed0mmAppliance other0mmMaximum angle w	When product panel is missing, set to 0	97	mm
Frontal handle thickness13mmFrontal handle width0mmMIN Height of the product body442mmMAX Height of the product body442mmWidth of the product body559mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMaximum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door6mmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally. At the side where the hinge is fixed0mmAppliance Side swing door0mmmmLateral projection of of poened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally. At the side where the hinge is fixed0mmAppliance other0mmmmDepth from front end of the niche to the front end of the freespace of the retrace0mmAppliance other0mmmmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm <td>Space in front, which is required to guarantee full operability. The most protruding part gives this dimension</td> <td>340</td> <td>mm</td>	Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	340	mm
Frontal handle width0mmMIN Height of the product body442mmMAX Height of the product body442mmWidth of the product body559mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiaterer maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door0mmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally. At the side where the hinge is fixed0mmAppliance Side swing door0mmmmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mmMaximum angle when door is opened totally0mmAppliance other0mmmmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mmAppliance other0mmmmMaximum ang	Height from bearing area of appliances and lower handle	344	mm
MIN Height of the product body442mmMAX Height of the product body549mmWidth of the product body543mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door0mmProjection of the opened flap in relation to bearing area0mmAppliance Side swing door6mmAppliance Side swing door0mmLateral projection of opened front incl. controls when door is opened totally. At the side where the hinge is fixed0mmAppliance other0mmDaximum angle when door is opened totally0mmAppliance other0mmDiater an projection of opened front at the side where the hinge is fixed0mmDuater and projection of opened front at the side where the hinge is fixed0mmDiater and projection of opened front at the side where the hinge is fixed0mmDiater and projection of opened front at the front end of the freespace of the retrace0 <td< td=""><td>Frontal handle thickness</td><td>13</td><td>mm</td></td<>	Frontal handle thickness	13	mm
MAX Height of the product body442mmWidth of the product body559mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmDameter minimum air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door11Projection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door11Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from tend of the niche to the front end of the freespace of the retrace0mmAppliance other0mmmmDiateral projection of other appliences from the sing end totaly. At the side where the hinge is0mmDiateral projection of opened front at the side where the hinge is fixed0mm </td <td>Frontal handle width</td> <td>0</td> <td>mm</td>	Frontal handle width	0	mm
Width of the product body559mmDepth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"NoProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDiateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally </td <td>MIN Height of the product body</td> <td>442</td> <td>mm</td>	MIN Height of the product body	442	mm
Depth of the product body543mmFull depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"No1Projection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDatateral projection of poneed front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDatateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDatateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when do	MAX Height of the product body	442	mm
Full depth of product excluding protruding interface elements563mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"0mmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totally. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened t	Width of the product body	559	mm
Minimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door6mmAppliance Side swing door6mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mm <tr <td="">Mm</tr>	Depth of the product body	543	mm
Maximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doorNoProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doormmmmLateral projection of popened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mmAppliance other0mmMaximum angle when door is opened totally0mmMaximum angle when doo	Full depth of product excluding protruding interface elements	563	mm
Diameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doorNoProjection of the opened flap in relation to bearing area6Maximum angle when flap door is opened totally85Appliance Side swing door0Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0Lateral projection of opened front at the side where the hinge is fixed0Maximum angle when door is opened totally0Maximum angle when door is opened totally0Depth from front end of the niche to the front end of the freespace of the retrace0	Minimum height from bottom line hood to top line air outlet	0	mm
Diameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doorNoProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mmOpenet front end of the niche to the front end of the retrace0mm	Maximum height from bottom line hood to top line air outlet	0	mm
Indicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doorNoProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Diameter minimum air outlet	0	mm
Projection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doormmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doormm85mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Diameter maximum air outlet	0	mm
Height tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoNoAppliance Flap door6mmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Indicates measure between center of air outlet hole and rear wall	0	mm
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doorImage: Second Sec	Projection of the rear flap in relation to bearing area	0	mm
Appliance Flap doorImage: Second	Height tube connection for air outlet	0	mm
Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally 85 mm Appliance Side swing door 85 mm Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No	
Maximum angle when flap door is opened totally 85 mm Appliance Side swing door 1 1 Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance Flap door		
Appliance Side swing door Image: Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Projection of the opened flap in relation to bearing area	6	mm
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Maximum angle when flap door is opened totally	85	mm
mounted Image: Constraint of the side where the hinge is fixed 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance Side swing door		
Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm
Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm
Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Maximum angle when door is opened totally	0	mm
	Appliance other		
Height from niche to bottom end of freespace for the retrace 0 mm	Depth from front end of the niche to the front end of the freespace of the retrace	0	mm
	Height from niche to bottom end of freespace for the retrace	0	mm